

Data Sheet

UDMAX™ GHDPE 46-70 XP001 TAPE (0.25 mm)

DESCRIPTION

UDMAX™ GHDPE 46-70 XP001 TAPE is a UD glass reinforced, polyethylene based, composite material, produced using UDMAX™'s proprietary HPFIT™ technology, delivering optimal fiber spreading and a resin-rich surface layer at high fiber contents. UDMAX™ GHDPE 46-70 XP001 TAPE has been developed for the thermoplastic composite piping market, easily sealing to HDPE liners resulting in composite pipes with excellent stiffness and strength. The standard color is black for optimal heat absorption. Please contact our customer service department for more information about available tape length and width, as well as winding method.

TYPICAL PROPERTIES VALUES

(Revision: 22092301)

Name	Typical values	Unit	Test methods
PHYSICAL			
Matrix material	HDPE		
Polymer melting point	128	°C	
Glass content	46	Volume%	-
Glass content	70	Weight%	-
Thickness	0.250	mm	-
Density	1.67	kg/dm ³	ISO1183
Areal weight	430	g/m ²	-
MECHANICAL			
Tensile modulus 0°	31	GPa	ISO 527-5
Tensile strength 0°	1050	MPa	ISO 527-5

PROCESSING

It is not necessary to dry UDMAX™ GPE 46-70 XP001TAPE prior to use. The recommended processing temperature range is 190° to 210°C. It is advised to allow newly shaped parts, produced using UDMAX™ GHDPE 46-70 XP001 TAPE, to cool down to 80°C or below, before further handling.

DISCLAIMER

Information and recommendations contained in this document are given in good faith. However, seller makes no express or implied representation, warranty or guarantee (i) that any results described in this document will be obtained under end use conditions, or (ii) as to the effectiveness or safety of any design or application incorporating seller's materials, products, services or recommendations. Brands marked with ™ are registered trademarks of UDMAX™ Tapes

UDMAX™ Tapes

Adress: OSB 4. cad No:4 26110 Eskişehir Turkey

T: +90 222 236 22 22

E: info@frttapes.com

W: www.frttapes.com

