

Data Sheet

UDMAX[®] GHDPE 40-65 XP011 TAPE (0.27 mm)

DESCRIPTION

UDMAX[™] GHDPE 40-65 XP011 TAPE is a UD glass reinforced, polyethylene based, composite material, produced using UDMAX[™]'s proprietary HPFITM technology, delivering optimal fiber spreading and a resin-rich surface layer at high fiber contents. UDMAX[™] GHDPE 40-65 XP011 TAPE has been developed for the thermoplastic composite piping market, easily sealing to HDPE liners resulting in composite pipes with excellent stiffness and strength. The standard color is black for optimal heat absorption. Please contact our customer service department for more information about available tape length and width, as well as winding method.

TYPICAL PROPERTIES VALUES

(Revision: 22092301)

Name	Typical values	Unit	Test methods
PHYSICAL			
Matrix material	HDPE		
Polymer melting point	132	°C	ISO 11357 -1/-3
Glass content	40	Volume%	-
Glass content	65	Weight%	-
Thickness	0.270	mm	-
Density	1.61	kg/dm ³	ISO1183
Areal weight	434	g/m ²	-
MECHANICAL			
Tensile modulus 0°	31	GPa	ISO 527-5
Tensile strength 0°	850	MPa	ISO 527-5

PROCESSING

It is not necessary to pre-dry UDMAX[®] GHDPE 40-65 XP011 TAPE prior to use. The recommended processing temperature range is 160° to 180°C

DISCLAIMER

Information and recommendations contained in this document are given in good faith. However, seller makes no express or implied representation, warranty or guarantee (i) that any results described in this document will be obtained under end use conditions, or (ii) as to the effectiveness or safety of any design or application incorporating seller's materials, products, services or recommendations. Brands marked with [™] are registered trademarks of UDMAX[™] Tapes

UDMAX[™] Tapes

Address: OSB 4. cad No:4 26110 Eskişehir Turkey

T: +90 222 236 22 22

E: info@frttapes.com

W: www.frttapes.com

